

# TIGRE

THE 15 SERIES



## TIGRE: little big friend



The Tigre is the most compact equal wheel tractor of the Antonio Carraro range. This fantastic "All rounder" was designed to satisfy a multitude of activities associated with the management of parks, gardens, sports fields, communal areas and small agricultural plots.

The features that set the Tigre models from the Series 15 apart are basically **reliability, comfort and safety**. In particular the Antonio Carraro full chassis with oscillation **ACTIO™** is synonymous with an equal weight distribution, maximum grip, minimum ground compaction, first class operative comfort.

The four wheel drive, along with **ACTIO™**, guarantee maximum comfort and operative safety in that they grant **constant traction and grip**.

The environmentally reliable 4 stroke diesel engine with 12 speed mechanical gearbox with 12 forward and 8 reverse speeds, offer a complete speed range in both directions, along with a substantial **saving in running costs**.

Its great versatility allows the operator to work in a variety of environments every day of the year; for this reason each owner of the Tigre will discover he has a **friend for all seasons**.





# TECHNICAL DATA: TIGRE 3200

## THE 15 SERIES



<b>Chassis</b>	ACTIO™ – Full chassis with oscillation • Steerable wheels • Four equal wheel drive				
<b>Engine Type</b>	Diesel indirect injection Emissions regulations: Stage 3A      N° cylinders: 3 Displacement cc: 1115      Output kW/HP (97/68/CE): 18/25 Max engine rpm: 3000      Max. torque (Nm/rpm): 67,8/2000 Cooling system: Water      Fuel tank capacity (l.) : 20				
<b>Transmission</b>	12-speed mechanical gearbox: 8 forward and 4 reverse speeds				
<b>PTO</b>	Standard at 540 rpm and synchronised with all gearbox speeds				
<b>Shaft</b>	ASAE profil 1" 3/8 with 6 splines				
<b>Rear hydraulic lift</b>	Rear with 3-point hitch (cat. 1) - Capacity (Kg): 950 Operating Pressure (bar)      140				
<b>Steering</b>	Hydraulic				
<b>Brakes</b>	Rear-axle and parking brakes				
<b>Tyres</b>	7.50-16	6.50-16	7.5L-15	29x12.50-15 STG	29x12.50-15 GARDEN
Min. ext. width (mm)	1155	1070	1110	1375	1375
Ground clearance (mm)	330	316	310	305	305
<b>Weight</b> in order of speed (Kg)	1000				
<b>Dimensions</b>	Wheelbase: 1100		Front overhang: 860		
	Lenght: 2640		Height: 1630		



### Standard equipment

- Front and rear independent differential lock
- Adjustable, sprung seat
- Safety belts
- Foldable safety roll bar
- Multiple-hole draw-bar
- Tow hook
- Horn
- Lights
- Power socket
- Braking and turning indicators
- Series of control lights
- Tachometer/revolution counter
- Safety starting switch

### Optional

- Rear revolving working light
- Wheel ballasts
- Single acting hydraulic outlet with rear quick coupling
- Mudguards widening for wide wheels

The description and illustrations in this brochure are provided simply for information purposes; they are not binding and may be varied at any time without notice



**ANTONIO CARRARO SPA**  
Via Caltana, 24  
35011 Campodarsego Padova ITALY  
info@antoniocarraro.it  
antoniocarraro.com  
COD. 4 7318 117 - 05/2014