

Subsoiler MOD. D.A.R.



WITH CURVED ANCHORS

- Double chassis to support anchors made of cut tube profile sizes: 120x120x8
- Fittings for lifting device adjustable in width for application to all tractors
- Anchors support adjustable in width to adjust the working width
- Special anchors safety bolt with anti-release bushing.
- Roller operation with tractor oil
- Smooth rear roller \varnothing 500 mounted on a bearing with hydraulic adjustment of the working depth of the anchors

MOD.	Nr of Anchors	\varnothing Roller	Kg	Tractor HP	Working Width (cm)	Working Depth (cm)	Price (€)	Price WITHOUT ROLLER (€)
D.A.R. 140	2	50	650	60-90	200-700	1400	1800	
D.A.R. 170	2	50	730	80-100	200-700	1700	2600	







Subsoiler Mod. D.A.R. C



With curved anchors - with fertilizer

- General characteristics: see above
- Equipped with container made of stainless steel with a load capacity of 450 lt.
- With hydraulic engine to turn over the fertilizer inside the container
- Hydraulic opening for the dosage of the product
- HAND CONTROLLER
- TRACTOR: 6 HYDRAULIC DOUBLE-EFFECT JACKS

MOD.	Nr of Anchors	Ø Roller	Kg	 HP				€
D.A.R. C 140	2	50	750	60-90	200-700	1400	1800	
D.A.R. C 170	2	50	890	80-100	200-700	1700	2600	

ACCESSORIES



OPEN-FURROW DISK

Cod. DAR001

1 disk Ø 330	
--------------	--

2 disks Ø 330	
---------------	--



TWO-WAY DIVERTER

Cod. DAR002

To control:

- The dosage of the product
- The depth roller